

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

Issue date: 12/2/2021 Revision date: 11/27/2023 Version: 1.2

SECTION 1: Identification of the hazardous chemical or mixture and of the supplier or manufacturer

1.1. GHS product identifier

Product form : Mixture
Trade name : HH-66 Vinyl Cement
Synonyms : PVC Vinyl Adhesive

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : ADHESIVES

1.4. Supplier's details

Supplier
RH Adhesives
308 Old High Street
01720 Acton, MA - USA
T 1-978-897-8000

1.5. Emergency phone number

Emergency number : 1-800-535-5053 INFOTRAC; 1-352-323-3500 INFOTRAC International

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS MX classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor.
Acute toxicity (oral) Category 5	H303	May be harmful if swallowed.
Skin corrosion/irritation Category 3	H316	Causes mild skin irritation.
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation.
Reproductive toxicity Category 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).
Hazardous to the aquatic environment - Acute Hazard Category 3	H402	Harmful to aquatic life.

Full text of H statements : see section 16

2.2. Label elements

GHS MX labelling

Hazard pictograms (GHS MX) :



Signal word (GHS MX) :

Danger

Hazard statements (GHS MX) :

H225 - Highly flammable liquid and vapor
H303 - May be harmful if swallowed
H316 - Causes mild skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

Precautionary statements (GHS MX)	: H361 - Suspected of damaging fertility or the unborn child H373 - May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation) H402 - Harmful to aquatic life P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P242 - Use only non-sparking tools. P243 - Take action to prevent static discharges. P260 - Do not breathe vapors, spray, mist. P264 - Wash hands, forearms and face thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P312 - Call a POISON CENTER or doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use carbon dioxide (CO2), alcohol resistant foam, dry extinguishing powder to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
-----------------------------------	---

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification	: This product or its emissions may aggravate already existing eye disorders. Respiratory complaints. Skin irritation, dermatitis and sensitization.
Adverse physicochemical, human health and environmental effects	: Highly flammable liquid and vapor,Suspected of damaging fertility or the unborn child,May cause damage to organs through prolonged or repeated exposure,May cause drowsiness or dizziness,Harmful if swallowed,Causes mild skin irritation,Causes serious eye irritation,Harmful to aquatic life

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

3.2. Mixtures

Name	Product identifier	%	GHS MX classification
Methyl ethyl ketone	CAS-No.: 78-93-3	≥ 40 – < 60	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Eye Irrit. 2, H319 STOT SE 3, H336
Acetone	CAS-No.: 67-64-1	≥ 25 – < 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Toluene	CAS-No.: 108-88-3	≥ 7 – < 10	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation. Lacrimation. Redness. Blurred vision. Eye irritation.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapor. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Heating will cause a rise in pressure with a risk of bursting. In case of fire and/or explosion do not breathe fumes.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

- Firefighting instructions : Move containers from fire area if it can be done without personal risk. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Evacuate the danger area. Eliminate all ignition sources if safe to do so.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Measures to be taken in case of accidental spillage or accidental leakage

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with skin and eyes. No flames, no sparks. Eliminate all sources of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel. Avoid breathing (dust, vapor, mist, gas). Use non-sparking tools.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Remove ignition sources. Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Storage area	: Store in dry, cool, well-ventilated area.
Incompatible products	: Strong acids. Strong bases. Oxidizing agent. Amines. Inorganic acids. Metallic salts.
Incompatible materials	: Direct sunlight. Sources of ignition.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl ethyl ketone (78-93-3)

Mexico - Occupational Exposure Limits

Local name	Metil etil cetona, MEK
OEL TWA [2]	200 ppm
OEL STEL [ppm]	300 ppm
Remark (MX)	Irritación del tracto respiratorio superior; daño a sistema nervioso central y periférico; IBE (Índice Biológico de Exposición recomendados por sustancia química)
Regulatory reference	NOM-010-STPS-2014

Mexico - Biological Exposure Indices

Local name	METIL ETIL CETONA (MEK)
BEI (BLV)	2 mg/l Parámetro: MEK - Medio: orina - Tiempo de muestreo: Al final del turno de trabajo
Regulatory reference	NOM-07-SSA1-2011

Acetone (67-64-1)

Mexico - Occupational Exposure Limits

Local name	Acetona
OEL TWA [2]	500 ppm
OEL STEL [ppm]	750 ppm
Remark (MX)	Irritación del tracto respiratorio superior y ojos; daño a sistema nervioso central; efecto hematológico; A4 (No clasificado como carcinógeno en humano Agente que puede ser cancerígeno para humanos pero que no puede ser concluyentemente asegurado por falta de datos. Estudios in vitro o animales no proveen indicaciones de carcinogenicidad suficientes para clasificar al agente en una de las otras categorías); IBE (Índice Biológico de Exposición recomendados por sustancia química)
Regulatory reference	NOM-010-STPS-2014

Mexico - Biological Exposure Indices

Local name	ACETONA
BEI (BLV)	50 mg/l Parámetro: Acetona - Medio: orina - Tiempo de muestreo: Al final del turno de trabajo - Observaciones: Ne
Regulatory reference	NOM-07-SSA1-2011

Toluene (108-88-3)

Mexico - Occupational Exposure Limits

Local name	Tolueno
------------	---------

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

Toluene (108-88-3)	
OEL TWA [2]	20 ppm
Remark (MX)	Daño visual; daño a órgano reproductor femenino; pérdida del embarazo; A4 (No clasificado como carcinógeno en humano Agente que puede ser cancerígeno para humanos pero que no puede ser concluyentemente asegurado por falta de datos. Estudios in vitro o animales no proveen indicaciones de carcinogenicidad suficientes para clasificar al agente en una de las otras categorías); IBE (Índice Biológico de Exposición recomendados por sustancia química)
Regulatory reference	NOM-010-STPS-2014
Mexico - Biological Exposure Indices	
Local name	TOLUENO
BEI (BLV)	1 mg/l Parámetro: o-Cresol - Medio: orina - Tiempo de muestreo: Al final del turno de trabajo - Observaciones: B 2 g/g Creatinin Parámetro: Acido hipúrico - Medio: orina - Tiempo de muestreo: Al final del turno de trabajo - Observaciones: B, Ne 0 mg/l Parámetro: Tolueno - Medio: sangre - Tiempo de muestreo: Previo al último turno de la semana detrabajo
Regulatory reference	NOM-07-SSA1-2011

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment : Wear recommended personal protective equipment.
Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : white
Odor : strong aromatic odor/sharp mint like fragrance
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : > 35 °C
Flash point : -14 °C (Method: ASTM D-56)
Flammability (solid, gas) : Not applicable
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : > 1 (heavier than air)
Relative density : 0.83 (water=1)
Density : 827.2 g/l
Solubility : insoluble in water.
Partition coefficient n-octanol/water (Log Pow) : No data available

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 1232 – 1408 mm ² /s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: Lower explosive limit (LEL): 1 vol % Upper explosive limit (UEL): 12 vol %

9.2. Other information

VOC content : 53 % (437 g/l)

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases. Amines. Inorganic acids. Metallic salts.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Other information : No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

11.1. Information on toxicological effects

Acute toxicity (oral)	: May be harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ATE MX (oral)	4088.294 mg/kg body weight
Methyl ethyl ketone (78-93-3)	
LD50 oral rat	2054 mg/kg
LD50 dermal rat	> 10 ml/kg
LD50 dermal rabbit	5000 mg/kg
LC50 Inhalation - Rat [ppm]	11700 ppm/4h
LC50 Inhalation - Rat (Vapours)	34.5 mg/l/4h
ATE MX (oral)	2054 mg/kg body weight

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

ATE MX (dermal)	5000 mg/kg body weight
ATE MX (gases)	11700 ppmV/4h
ATE MX (vapors)	34.5 mg/l/4h

Acetone (67-64-1)

LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	15688 mg/kg
LC50 Inhalation - Rat	44 g/m ³
ATE MX (oral)	5800 mg/kg body weight
ATE MX (dermal)	15688 mg/kg body weight
ATE MX (vapors)	44 mg/l/4h
ATE MX (dust, mist)	44 mg/l/4h

Toluene (108-88-3)

LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 Inhalation - Rat	25.7 mg/l/4h
ATE MX (oral)	2600 mg/kg body weight
ATE MX (dermal)	12000 mg/kg body weight
ATE MX (vapors)	25.7 mg/l/4h
ATE MX (dust, mist)	25.7 mg/l/4h

Skin corrosion/irritation	: Causes mild skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.

Methyl ethyl ketone (78-93-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Acetone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).

Toluene (108-88-3)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Methyl ethyl ketone (78-93-3)

LC50 - Fish [1]	3130 – 3320 mg/l (Exposure time: 96 h; Species: Pimephales promelas; flow-through)
EC50 - Crustacea [1]	520 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	5091 (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic algae	93 mg/l
Partition coefficient n-octanol/water (Log Pow)	0.29

Acetone (67-64-1)

LC50 - Fish [1]	4144.846 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
LC50 - Fish [2]	6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [Static])
EC50 - Crustacea [1]	1679.66 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
BCF - Fish [1]	0.69
Partition coefficient n-octanol/water (Log Pow)	-0.24

Toluene (108-88-3)

LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 433 mg/l (Pseudokirchneriella subcapitata)
EC50 72h - Algae [2]	12.5 mg/l (Pseudokirchneriella subcapitata)
NOEC chronic fish	1.4 mg/l (Oncorhynchus kisutch)
NOEC chronic crustacea	0.74 mg/l (Ceriodaphnia dubia)
Partition coefficient n-octanol/water (Log Pow)	2.7

12.2. Persistence and degradability

HH-66 Vinyl Cement

Persistence and degradability	Biodegradability in water: no data available.
-------------------------------	---

Acetone (67-64-1)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

12.3. Bioaccumulative potential

HH-66 Vinyl Cement	
Bioaccumulative potential	No data available concerning bioaccumulation.
Methyl ethyl ketone (78-93-3)	
Partition coefficient n-octanol/water (Log Pow)	0.29
Acetone (67-64-1)	
BCF - Fish [1]	0.69
Partition coefficient n-octanol/water (Log Pow)	-0.24
Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.7

12.4. Mobility in soil

HH-66 Vinyl Cement	
Ecology - soil	Adsorbs into the soil.
Methyl ethyl ketone (78-93-3)	
Partition coefficient n-octanol/water (Log Pow)	0.29
Acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Pow)	-0.24
Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.7

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not dispose of the packaging without first carrying out the necessary cleaning. Do not pierce or burn, even after use.
Ecology - waste materials	: Avoid release to the environment.
Additional information	: Flammable vapors may accumulate in the container.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with NOM / UN RTDG / IMDG / IATA

14.1. UN number

UN-No. (NOM/SCT)	: 1133
UN-No.(UN RTDG)	: 1133

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

UN-No. (IMDG) : 1133
UN-No. (IATA) : 1133

14.2. UN proper shipping name

Proper Shipping Name (NOM/SCT) : ADHESIVOS que contengan líquidos inflamables
Proper Shipping Name (UN RTDG) : ADHESIVOS
Proper Shipping Name (IMDG) : ADHESIVES
Proper Shipping Name (IATA) : Adhesives

14.3. Transport hazard class(es)

NOM

Transport hazard class(es) (NOM) : 3
Danger labels (NOM/SCT) : 3
:



UN RTDG

Transport hazard class(es) (UN RTDG) : 3
Hazard labels (UN RTDG) : 3
:



IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3
:



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3
:



14.4. Packing group

Packing group (NOM/SCT) : II
Packing group (UN RTDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

14.6. Special precautions for user

NOM	
Limited quantities (NOM/SCT)	: 5L
Excepted quantities (NOM/SCT)	: E2
Packing instruction (NOM/SCT)	: P001, IBC02
Special packing provisions (NOM/SCT)	: PP1
Portable tank and bulk container instructions (NOM/SCT)	: T4
Portable tank and bulk container special provisions (NOM/SCT)	: TP1, TP8
UN RTDG	
Limited quantities (UN RTDG)	: 5L
Excepted quantities (UN RTDG)	: E2
Packing instruction (UN RTDG)	: P001, IBC02
Special packing provisions (UN RTDG)	: PP1
Portable tank and bulk container special instructions (UN RTDG)	: T4
Portable tank and bulk container special provisions (UN RTDG)	: TP1, TP8
IMDG	
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.
IATA	
PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A3
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Methyl ethyl ketone (78-93-3):

Listed in the INSQ (National Inventory of Chemical Substances)

Acetone (67-64-1):

Listed in the INSQ (National Inventory of Chemical Substances)

International regulations

Methyl ethyl ketone (78-93-3):

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not subject to reporting requirements of the United States SARA Section 313
Listed on the Canadian DSL (Domestic Substances List)
Listed on EPA Hazardous Air Pollutant (HAPS)

Acetone (67-64-1):

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not subject to reporting requirements of the United States SARA Section 313
Listed on the Canadian DSL (Domestic Substances List)

Toluene (108-88-3):

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313
Listed on the Canadian DSL (Domestic Substances List)
Listed on EPA Hazardous Air Pollutant (HAPS)

SECTION 16: Other information including those related to the preparation and updating of safety data sheets

Revision date : 11/27/2023

Full text of H-phrases

H225	Highly flammable liquid and vapor
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways
H313	May be harmful in contact with skin
H315	Causes skin irritation
H316	Causes mild skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

HH-66 Vinyl Cement

Safety Data Sheet

According to the NOM-018-STPS-2015

Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.
Other information : SDS prepared by. H2 Compliance.

Safety Data Sheet (SDS), Mexico

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.